

BAKERS FORKLIFT SERVICES LTD
T/A BFS FORKS & ATTACHMENTS
 2 HAINGE ROAD, TIVIDALE, OLDBURY, B69 2NH
 TEL: 0121 557 1935 FAX: 0121 557 4245
 E MAIL: SALES@BFSLTD.CO.UK

FORK EXTENSION SLEEVES



Quick and easy to fit, fork extension sleeves are designed to extend the trucks "normal" length forks, allowing long or out of reach loads to be handled. Features: (i) heavy duty pressed construction, (ii) tapered and shaped tips and (iii) rounded edges. Fork length must be minimum 60% of length of fork extension.

Safe Working Load (SWL) = truck capacity at extended load centre (normally ½ sleeve length).

Our standard range sleeve thickness is 73 mm, maximum fork thickness is 65 mm and are available any length up to 2500 mm.

"Stirrup" type extension sleeves are normally supplied for forks having 76 mm drop or less eg. FEM 2A and 3A. Loose pin type for all forks having or 76 mm drop eg. FEM 2B, 3B, 4A, Reach and Bar Type. Longer, larger and special extensions eg. Semi-circular and triangular are available to order.

TECHNICAL DATA

Model No	Extension length mm up to	Fork Width mm	Weight kgs
X1500-80	1500	80	43
X2000-80	2000	80	57
X1500-100	1500	100	46
X2000-100	2000	100	62
X2500-100	2500	100	77
X1500-125	1500	125	51
X2000-125	2000	125	68
X2500-125	1500	150	56
X1500-150	1500	150	56
X2000-150	2000	150	74
X2500-150	2500	150	93

DESIGN, MANUFACTURE, REPAIR, MPI CRACK TEST AND PROOF LOAD TEST
FORKLIFT FORKS & ATTACHMENTS
STANDARD ATTACHMENT RANGE INCLUDES:
EXTENSION SLEEVES, SAFE ACCESS PLATFORMS, DRUM CLAMPS, JIBS,
LONG REACH SCOOPS, ROLL FORWARD SKIPS, CARPET/COIL BOOMS